



TEGERA® 126A

Welding and heat-resistant glove, unlined, 0,7-0,8 mm full grain goatskin of top quality, Cat. II, white, yellow, withstands contact heat up to 100°C, reinforced seams, elasticated 180°, for assembly work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, extra flexible, durable, perfect fit

SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. II

SIZE RANGE 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,7-0,8 mm

BACK MATERIAL Full grain goatskin of top quality

LINING Unlined

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 310-350 mm

COLOUR White, yellow

PAIRS PER PACKAGE/CARTON 12/60

DISPLAY Thread

MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
7	126a-7	7340118312293
8	126a-8	7340118312316
9	126a-9	7340118312330
10	126a-10	7340118312255
11	126a-11	7340118312279

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 126A

FEATURES

Withstands contact heat up to 100°C, reinforced index finger, reinforced seams

PRIMARY PROTECTION

Prevents risk of: burn injuries, heat injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

All-year use, warm environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Assembly, engineering, metalwork, welding, hot work, mining

PRIMARY INDUSTRIES OF USE



Mining, oil, gas, petrochemical, metal fabrication, automotive

TYPE OF WORK

Light weight

2(3)

 Cat. II

 EN 388 2111  EN 407 412X4X EN 12477 + A1 Type B EN 1149-2 R:2.55x10⁵Ω



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-08-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 126A

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to wear (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection	1	2	3	4	5
A) Resistance to wear (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)




EN 12477:2001 + A1:2005 Protective gloves for welders

Type B - Higher dexterity (with lower other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE Cat. II

 EN 388 2111
  EN 407 412X4X
 EN 12477 + A1 Type B
  EN 1149-2 R:2.55x10⁶Ω



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-08-15

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com